

Intro to Passive House Trades

Ken Levenson – Passive House Network


August 14, 2025






Zoom Orientation

- Add an introduction in the chat.
 Be sure full name is displayed.
- Did you call in? Please share first and last name with us.
- Please mute upon joining
- Use the "Chat" to share questions or comments
- Under "Participant" select "Raise Hand" to share a question or comment verbally
- Session may be recorded and posted to 3C-REN's on-demand page
- Slides/recording are shared after most events
- 3C-REN does not allow Al notetakers, unless used to accommodate a disability.





Tri-County Regional Energy Network

3C-REN is a collaboration between the tri-counties

Our programs reduce energy use for a more sustainable, equitable and economically vibrant Central Coast

Our free services are funded via the CPUC, bringing ratepayer dollars back to the region

Our Services

Incentives



HOME ENERGY SAVINGS

3c-ren.org/for-residents 3c-ren.org/multifamily



3c-ren.org/commercial

Contractors can enroll at **3c-ren.org/contractors**

Training



BUILDING PERFORMANCE TRAINING

3c-ren.org/events 3c-ren.org/building



3c-ren.org/code

View past trainings at **3c-ren.org/on-demand**

Technical Assistance



AGRICULTURE ENERGY SOLUTIONS

3c-ren.org/agriculture



ENERGY ASSURANCE SERVICES


3c-ren.org/assurance



PASSIVE DESIGN/BUILD™ BOOTCAMP

REGISTER TODAY!

Ventura, CA Sep 29 - Oct 3, 2025





PASSIVE DESIGN/BUILD™ BOOTCAMP

REGISTER TODAY!

Typical Audience

- Builders, General Contractors
- Architects, Designers
- Construction Professionals

Registration

- Upon approval, tuition fees are covered by 3C-REN for professionals operating in the counties of Santa Barbara, San Luis Obispo, and Ventura (scan QR code for more info)
- Some spots available for purchase for participants from outside the 3C-REN territory (\$2490/person)





Format: In-person

Typical Schedule:

- Building Science Course Sep 29+30
- Hands-on Workshop Oct 1+2
- Passive House Certification Exam Oct 3

Application Deadline: Sep 19

In-person days are 8am-5pm
Lunches are provided (Mon-Thu)





Format: **Hybrid**

Typical Schedule:

- Building Science Course 16hr self-paced on-demand, before coming in for the hands-on workshop
- Hands-on Workshop Oct 1+2
- Passive House Certification Exam Oct 3

Application Deadline: Sep 1







Sendero Verde, Handel Architects

Introduction to Passive House Trades

www.passivehousenetwork.org

The Network Global Knowledge. Regional Context. Local Applications





















































Passive House Washington DC










































Climate Disaster Support



Design Competition

Submission Deadline, September 30th



Tuesday, November 4th







...to develop a groundbreaking catalog of high-performance homes to inspire and inform the rebuilding efforts in the aftermath of the Eaton and Palisades Fires.

Certified Professionals





Financial incentives available.

Pacific Cohort Schedule

Fall 2025 - On-Demand / Live Online CPHD/C Training

October 2nd start

- Depending on your learning preferences, you can tackle this course in three ways:

 1. Focus on the on-demand content and view recordings of live online content. (Most flexible)

 2. Stick to the cohort schedule of live online sessions. (Best for clear pacing and making connections and community)
- Do a mixl Start before or after the cohort registration deadline, focus on the on-demand format at your pace, and attend the live online sessions as makes sense for you. (Most

On-Demand		Live Online Activities			
Week Starts	Content	Activity Date/Time	Activity	Led by	
9/29/25	Module 1: Introduction Module 2: Insulation	10/2/25 12-1 PM PT	Kick-Off	PHN	
10/6/25	Module 3: Airtightness Module 4: Thermal Bridging Module 5: Windows	10/9/25 12-1 PM PT	Q&A Session 1	CPHD Practitioner	
10/13/25	Webinar 1: Building Envelope Module 6: Ventilation	10/16/25 9-12 PM PT	Webinar 1: Building Envelope	PHN Trainer	
10/20/25	Module 7: Heating & DWH Module 8: Cooling Module 9: Certification	10/23/25 9-11:30 AM PT	Open Review	Ken Levenson	
10/27/25	Module 10: Economics Module 11: QA/QC Module 12: Bidding	10/30/25 12-1 PM PT	Q&A Session 2	CPHD Practitioner	
11/3/25	Webinar 2: Building Services & Economics Review Exam Prep Modules	11/6/25 9-12 PM PT	Webinar 2: Building Services & Economics	PHN Trainer	
11/10/25	Module 13: designPH Module 14: PHPP Review Exam Prep Modules	-		-	
11/17/25	Module 15: Exam Prep Course & Wrap-up Review Exam Prep Modules	-	(2)	-	
11/24/25	Review Exam Prep Modules	11/25/25 9-11 AM PT	Exam Review	PHN Trainer	
12/1/25	Review Exam Prep Modules	12/4/25 9-10 AM PT	Tech Setup (Required)	PHN with PHA	
12/8/25	Exam	12/11/25 9-12 PM PT	PHI CPHD/C Exam	PHN with PHA	

Agenda

- 1. Intro to Passive House
- 2. Passive House Criteria
- 3. Team & Process Overview
- 4. Enclosure
- 5. Mechanical Systems
- 6. QA/QC
- 7. Resources



Introduction to Passive House Trades

PHN's Introduction to Passive House Trades course is a comprehensive dive into constructing residential and commercial Passive House buildings, specifically at the enclosure and mechanical trades.

There will be a brief introduction to Passive House about the basic principles and the drivers of Passive House performance that most concern builders' work.

The enclosure section will look at typical construction types, windows and installation, air barriers and insulation, and new, innovative PH products. The mechanical will look at the ventilation heating, cooling systems, and domestic hot water.

The work of the trades will be clearly placed in the context of Passive House performance, the role of each aspect of construction, its sequencing - and the importance of the tradesperson's work in achieving the target goals.

2 AIA LUs Credit, #IntroTrades2hr

Learning Objectives:

- 1. Describe the five key principles of Passive House projects.
- Summarize typical materials, methods, and components used in Passive House enclosures and mechanical systems.
- 3. Outline typical Passive House construction sequencing.
- 4. Describe the basic approach to quality control, verification and commissioning.

Introductions

Please answer questions in the comments:

- 1. Name? (if you'd like)
- 2. Location?
- 3. Typical project role/background?
- 4. Any previous Passive House knowledge or experience? If so, what?

Personal Start: A Townhouse Retrofit





Brooklyn, NY


Intro to Passive House



How we use fundamental elements matters


"I was working as a physicist. I read that the construction industry had experimented with adding insulation to new buildings and that energy consumption had failed to reduce. This offended me – it was counter to the basic laws of physics. I knew that they must be doing something wrong. So I made it my mission to find out what, and to establish what was needed to do it right."

- Wolfgang Feist



Passive House masters the elements of high-performance building.

What is Passive House?









- Passive House is a building standard
- Applies to new & existing buildings
- The most rigorous energy efficiency certification available
- Performance-based approach
- Focuses on mastering the drivers of building performance.

Project Types – Not Just Houses!



The House at Cornell Tech



Star Garment Factory



Betances V

Goals of Passive House

- Thermal Comfort
- Hygienic conditions
 - No mold
 - Healthy indoor air quality
- Energy Efficiency
- Durability

+


Affordability







Wildfire Resilience





Passive House delivers high-quality homes that are healthy, comfortable, efficient, and resilient. Passive house characteristics can also make your home more resistant to wildfire and smoke damage.

Here's how:

1. A Simpler Form

With fewer enclosure junctions, such as the ins and outs of dormers, eaves, overhangs, rooflines, and floorplans, a simpler form denies burning embers the opportunity to lodge in the building construction.

2. Continuous Insulation

Installed like a protective blanket around the entire structure, non-combustible insulation can shield the building from fire and deny the fire its fuel.

3. Airtightness

The airtight enclosure keeps wind-driven burning embers and smoke out.

4. High-Performance Windows

Triple-pane windows, surrounded by robust frames, provide views, daylight, natural ventilation, and fire protection.

5. High-Performance Ventilation System

Filtered fresh air is continuously supplied while exhausting the stale air, providing healthy indoor air quality in polluted, smoky surroundings.



Be sure to take other common-sense measures like eliminating fossil fuels, using Class A fireresistant materials at the exterior, and surrounding your home with fire-smart landscaping. Facing extreme conditions, let's design and build for a resilient future with Passive House.

isthe_phnetwork The Passive House Netwo


....


Plus:

Class A fire Spread rated materials Vulcan Vents at eaves Landscaping




Andrew Michler, Hyperlocal Workshop








5 Principles of Construction (the drivers)




These are the 5 things builders must focus on most intently.


Energy Modeling: Calculating Predictable Performance



Predictable Performance is THE thing.



Right size Heating & Cooling Systems



Single Family: Los Angeles

- 1791 SF
- Heating load 1850 BTU/540 watts
- Cooling load 5400 BTU/1580 watts
- Net Zero with 9kW Solar PV









Credit: Paravant Architects

Construction is complicated!



So many demands:

- Structural
- MEP
- Life safety
- Environmental
- Worker safety
- Framing
- Finishes
- Sequencing
- Budgets
- Other certifications!
- etc...

Passive House Focus: Hygiene, Comfort and Efficiency

What Trades to Focus on

- Carpentry
- Masonry
- Steel
- Foundation work
- Heating, Cooling & Ventilation
- Plumbing
- Electrical
- Verification, Testing & Commissioning



Each should have a general understanding of Passive House & specific knowledge of their works impact. Connect the work to final performance results.

Logic of Passive House




Focus makes high quality affordable


Anyone can build Passive House with modest but specific training.

It's more about building intentionally and simply.



Access what's available: Project documentation, Certified Components, Manufacturer Directory







Manufacturer/Supplie


Manufacturer/Supplier	Specialty	Offers PHI Certified Components	HQ Location	Link
Delta Dorken			Canada	https://www.darken.com/en/
Hanno		Yes	Germany	https://worldclasssupply.com/
Intelligent Membranes		Yes	UK	https://www.inteligentmembranes.com/
Partel		Yes	Ireland/NY	https://www.partel.com/
Pro Clima		Yes	Germany/NY	https://475.supply/collections/pro-clima
Prosoco		10000	Kansas	https://prosoco.com/
Retrotec	blower door		Washington	https://retrolec.com/
Rothoblass		Yes	Italy	https://www.rothoblass.com/
Sign		Yes	New York	https://www.siga.owice/us_en/products
Soprema			Ohio	https://www.soprema.us/
Stego	dela dua		Califormia	https://www.stegpindustries.com/
VaproShield			Washington	https://vaproshield.com/


manufacturer/ auppenr	apeciaty	Components		Line
Delta Dorken			Canada	https://www.darken.com/en/
Hanno		Yes	Germany	https://worldclasssupply.com/
Intelligent Membranes		Yes	UK	https://www.intelligentmembranes.com/
Partel		Yes	Ireland/NY	https://www.partel.com/
Pro Clima		Yes	Germany/NY	https://475.supply/collections/pro-clima
Prosoco			Kansas	https://presece.com/
Retrotec	blower door		Washington	https://retrotec.com/
Rothoblass		Yes	Italy	https://www.rothoblass.com/
Sign		Yes	New York	https://www.sigs.owios/us_en/products
Soprema			Ohio	https://www.soprema.us/
Stego	sub slab		Catiformia	https://www.stegoindustries.com/
VaproShield			Washington	https://vaproshield.com/
TEC (Minneapolis Blower Door)	blower door		Minnesota	https://www.energyconservatory.com/

WINDOWS, DOORS & SHADING SYSTEMS


Manufacturer/Supplier	Specialty	Offers PHI Certified Components	HQ Location	Link
Alpen		Yes	Colorado	https://www.thinkulpen.com/
Amberline			Massachussetts	https://amberlinewindows.us/
Bewiso	simulated double- hung		Austria/NY	http://www.bowiss.ou/
Cardinal	glazing, spacers	Yes	Minnesota	https://www.cardinalcorp.com/
Cascadia	fiberglass		British Columbia	https://www.cascadiawindows.com/
Deceuninck		Yes	Ohio	https://deceurinckna.com/
Eco Windows			Connecticut	https://ecowindowsusa.com/
Edge-Tech	spacers		Texas	https://www.quanex.com/product/for-architects/warm-edge spacers/
ENERsign		Yes	Germany/CO	https://www.enersign.com/en/
EuroLine Windows		Yes	British Columbia	https://euroline-windows.com/
Fakro	skylights		Potand/Itlinois	https://shop.fakrouss.com/
Garrma North America		Yes	Ontario	https://gammana.com/
GlassCurtain	curtain wall		Alberta	https://glasourtain.ca/
Hella	exterior shading	Yes	Germany/MN	https://www.tannerbp.com/hella-exterior-blinds
Ikan Windows			New York	https://www.korwindows.com/
Inline Fiberglass			Ontario	https://www.inlinefiberglass.com/
innotech Windows		Yes	British Columbia	https://www.inrotech-windows.com/

Books and more





























And more...



















The Passive House Criteria



Criteria: Goals









- 1. Occupant Health
- 2. Thermal Comfort
- 3. Energy Efficient
- 4. Durable
 - + Affordable

Criteria: Enclosure Quality

Thermal Protection (COMFORT)


EXT.

- Interior Surface Temperatures: not more than 7.6 F below the operative indoor temperature.
- Floors: not below 66.2 F, Checked against 71.6 F in PHPP

INT. 65°F 64.4°F Source: PHI No cold air drafts, no "cold feet"

Moisture Protection (HYGIENE/HEALTH)

fRsi defines the coldest point which can occur on the interior surface of a construction system. For example, if the temperature factor is 0.7, then 70% of the temperature difference between the inside and outside air is still present at the interior surface. If the temperature factor is achieved, then mould and condensation formation can be safely prevented at normal outdoor temperatures, indoor temperatures and indoor air humidity levels.




Even internal surface temperatures - Details matter a lot!

Criteria: Enclosure Quality

Airtightness (Health, Comfort & Durability)

- Whole building test result of equal or less than 0.60 ACH50.
- Average of depressurization & pressurization.







Airtight Building Envelope



Description of airtight cover

Air barrier spans the concrete slab on grade, transitions to the metal wall panel that has an interior air and vapor barrier which transitions to the concrete roof slab


0.13 ACH50 final test = 0.15 CFM/SF

Criteria: High-Performance Windows & Doors

- Airtight
- Excellent thermal performance
- Interior Surface Temperatures: not more than 7.6 F
 below the operative indoor temperature.










Criteria: Ventilation


- Sufficient filtered fresh air to all occupied spaces
- 2. User control and boost
- 3. 75% min system heat recovery efficiency
- 4. Fan power efficiency < 0.765 W/CFM
- 5. Balanced Flow: <10% disbalance between fresh air supply and exhaust air.















Criteria: Other MEP

Heating & Cooling:

- No hard rules but must be efficient.
- 2. While heat pumps are now common any type of system is possible.
- 3. Typical successful approaches.
 - a. Keep it simple and small (right sized):
 - b. Combined heat/cooling systems
 - c. Minimize refrigerant lines.

Domestic Hot Water:

- Efficient piping layout minimizing circulation.
- Well insulated hot water piping & accessories.
- 3. Efficient heater: Heat pump encouraged.
- 4. Efficient pumps.
- 5. Bath waste water heat recovery encouraged.

Appliances & Lighting:

- 1. Efficient appliances and lighting.
- 2. All-electric encouraged.

"Do no harm": Minimize "accidental" heating & cooling. Only use what you need.

Criteria: Energy (energy limits drive health & comfort)







Table 1 Passive House criteria





















Renovation Energy Criteria: EnerPHit

Table 3 EnerPHit energy demand criteria (as an alternative to Table 2)

	Heating	Cooling Max. cooling + dehumidification demand		
Climate zone according	Max. heating demand			
to PHPP	[kBTU/(ft²yr)]	[kBTU/(ft²yr)]		
Arctic	11.09			
Cold	9.51			
Cool- temperate	7.92	equal to		
Warm- temperate	6.34	Passive House requirement ₁		
Warm	4.75			
Hot	-			
Very hot				


or

Table 2 EnerPHit component criteria

	Opaque envelope ¹ against				Windows (including exterior doors)						
Climate zone	groundambient air				Overall ⁴ Glazing ⁵			Solar load ⁶	Ventilation		
	Insu- lation	Exterior insulation	Interior in- sulation ²	Exterior paint ³	Max. heat transfer			Solar heat gain	Max. specific solar		Min. hu- midity re
according to PHPP	Min. thermal resistance (R-value)			Cool	100	J _{D/W,insta}		coefficient (SHGC)	load during cooling period	very rate ⁷	covery rate ⁸
	[hr.ft².°F/BTU]			-	- [BTU/hr.ft².°F]		-	[kBTU/(ft²yr)]	%		
					\subset						
Arctic	Deter- mined in	63.09	22.71		0.08	0.09	0.11	U_g - SHGC*0.7 ≤ 0		80%	- 5
Cold		47.32	18.93	2	0.11	0.12	0.14	U _g - SHGC*1.0 ≤ 0		80%	-
Cool- temperate	PHPP from	37.86	16.22	-	0.15	0.18	0.19	U _g - SHGC*1.6 ≤ 0		75%	
Warm- temperate	project specific heating	18.93	11.36	-	0.18	0.19	0.21	U _g - SHGC*3.2 ≤ -0.6	32	75%	-
Warm	and cooling	11.36	7.57	-	0.22	0.23	0.25	-		-	-
Hot	degree days against ground.	11.36	7.57	Yes	0.22	0.23	0.25	÷		122	60 % (humid climate)
Very hot		22.71	12.62	Yes	0.18	0.19	0.21				60 % (humid climate)

plus

Table 4 General EnerPHit criteria (always applicable irrespective of the chosen method)



30+ Certifiers Working in the US

Active Certifiers in the US include:

- **CertiPHIers Cooperative**
- **Emu Passive**
- 3. Herz & Lang
- **Home Energy Services** 4.
- **Passive House Academy**
- 6. **Passive House Institute**
- **Peel Passive House**
- **RDH Building Science**
- Steven Winter Assoc





NACC MEMBERS

next building project:

US Based Members

CertiPHiers Cooperative www.certiphiers.com

www.emu.systems

Home Energy Services green-mann.com

Steven Winter Associates

Canada Based Members Mizu Passive House Consulting

Peel Passive House Consulting

RDH Building Science Inc. www.rdh.com

Stich Consulting & Design

Europe Based Members Herz & Lang www.herz-lang.de

www.meadconsulting.co.uk

www.passivehouseacademy.com Passive House Institute passivehouse.com

Passive House Academy

praxis-rb.com Zephir Passivhaus Italia passivhausitalia.com

stichpassivedesign.com

Find a NACC member for your

Benefits of Certification The North American Certifiers Circle (NACC) certification provides many benefits to the developer, designer, consultant, builder, owner, and others. Review services provided by a certifier are separate and distinct from those of a Passive House consultant or designer. This ensures an independent and objective assessment as well as additional quality assurance that benefits

Avoid False Starts By working with a certifier from the start of the project the project can benefit from the experience and institutional knowledge of the certifier.

avoiding rookie mistakes that need to be later undone. Professional Development for Project Teams The review of energy calculations and design and construction documentation

through the lens of experts in high-performance building allows other members of the project team to gain a new perspective.

Assurance for the Project Team Consultants decigners and builders alike can breathe easier knowing their

energy calculations and related details have been double-checked before construction begins.

all parties involved

We have established that the biggest driver of additional costs for Passive House is the experience or inexperience of the project team. No one has more experience than the building certifiers. Consequently the four reasons above work together to help you contain costs and meet your budget.



An initiative of Passive House Canada, The Passive House Network and the NACC members.

Other accredited Passive House certifiers



The following experts* have been internationally accredited by the Passive House Institute to certify Passive House buildings. EnerPHit retrofits and Low Energy Buildings anywhere in the world on behalf of the Passive House Institute and in accordance with their criteria

How to become a Passive House certifier

* Unless otherwise stated, building certification contracts are always concluded between the Passive House Institute and an individual person

Organisation ¢	Country *	Website ¢	Building Certifier		
CertiPHIers Cooperative, Inc.	United States of America	http://www.certiphiers.com	Matthew Bowers, Languages: en Tad Everhart, Languages: en Rolf Jacobson, Languages: en Chris Pett, Languages: en Ohristina Snyder, Languages: en		
Emu Building Science LLC	United States of America	https://emu.systems/	Enrico Bonilauri, Languages: en		
Home Energy Services	United States of America	http://www.green-mann.com	Steve Mann, Languages: en		
Steven Winter Associates, Inc	United States of America	http://www.swinter.com	Lois Arena, Languages: en		
Etude Consulting Ltd.	United Kingdom/ Britain	http://passivhaus.etude.uk passivhaus.certification@etude.uk	Naomi Grint, Languages: en Will South, Languages: en Chris Worboys, Languages: en		
Mead Energy & Architectural Design LTD	United Kingdom/ Britain	http://www.meadconsulting.co.uk	Kym Mead, Languages: en		
WARM - Low Energy Building Practice	United Kingdom/ Britain	http://www.peterwarm.co.uk	Sally Godber, Languages: en Liam McDonagh- Greaves, Languages: en Mike Roe, Languages: en Peter Warm, Languages: en		
ZE Passivhaus Services Ltd	United Kingdom/ Britain	https://www.passiv.org	Jesus Menendez Amigo, Languages: es en		
Passivhusbyrån Ingo Theoboldt	Sweden	http://www.passivhusbyran.se	Ingo Theoboldt, Languages: de en sv.		

https://passivehouse.com/03 certification/02 certification buildings/03 certifiers/01 accr edited/01 accredited.html

https://passivehousenetwork.org/wp-content/upload s/2023/01/NACC-Brochure-Jan-2023.pdf

Certified Passive House Components



https://database.passivehouse.com/en/components/

Certified Professionals



The on-demand and hybrid formats allow students to leverage the benefits of on-demand & live online training to best meet their learning preferences.

35 AIA LU/HSW credits

https://passivehousenetwork.org/designer-training/








https://passivehousenetwork.org/tradesperson-training/

Criteria Goals in Summary









- I. Occupant Health
- 2. Thermal Comfort
- 3. Energy Efficient
- 4. Durable
- + Affordable



- 1. Interior Surface Temperatures
- 2. Airtightness
- 3. Ventilation
- 4. Efficient MEP

Team & Process Overview



Assemble the team to deliver a Passive House

- Architects
- Engineers
- Consultants
- Passive House Consultant
- Builder & Trades
- Verifier/Verification
 - Inspectors
 - Ventilation Commissioning
 - Blower door testers
- Certifier

What a team needs:

- common language
- 2. common goal: Passive House
- 3. good attitudes
- 4. enough training
- willingness to work as a team and connect the dots











Certification Process Overview

The basic programming complete, engage a Certifier, and have the Certifier conduct an **initial check** of programmatic assumptions and certification criteria - to clarify how aspects will be

Initial Check

assessed in the

certification.

Planning/Pre-Design

Preliminary Review SD/DD Phase(s)

Design Stage Review
Construction Document Phase

Final Review Construction Completion

- 1. Assessment of the concepts for the design, insulation and building services, and of the preliminary version of the PHPP calculation for consistency with the certification criteria.
- 2. The PH consultant assembles key information.
 3. The Certifier will provide
- **3.** The Certifier will provide **feedback and suggestions** so you can optimize your design and specifications and update the PHPP energy model.

- 1. The PH consultant will prepare the detailed certification submittal package (PHPP, plans, specifications, and required supporting documentation) according to your Certifier's guidance.
- 2. Make corrections to your Certifier requests and re-submit until your Certifier can conditionally assure certification when construction is completed.
- 3. Your Certifier will issue a design stage assurance letter that, as designed, the building can be certified.

- **1.** Upon completion, **make submissions** for Certifier's final review.
- As-built PHPP energy model and plans per PHI certification protocols
- Photo documentation per PHI certification protocols.
- Blower door test results per PHI certification protocols.
- Ventilation system commissioning report per PHI certification protocols.
- Executed Builder Assurance Certificate that building has been constructed to the as-built plans and energy model per PHI certification protocols.
- **2.** If your building meets all certification criteria, you will receive the building certificate.
- **3.**Post the certificate on your website and attach the plaque to your new Passive House building.
- **4.** List your newly certified building in PHI's online international project directory.


Think about what makes quality control easier or harder each step of the way.

Introduction to Passive House Trades

Enclosure

Principles 1-4

First 4 Principles are about the enclosure



https://passipedia.org/basics/what is a passive house

Any Construction Type Can be Passive House












Introduction to Passive House Trades


Passive House is enclosure system agnostic

- Wood
- Metal
- Concrete


Build with what your teams know.



Wood Framed Walls




Metal Framed Walls



Concrete Walls

Enclosure systems





Collective Carpentry

ENCLOSURE SYSTEMS

Manufacturer/Supplier	Specialty	Offers PHI Certified	HQ Location	Link
		Components		
B.Public Prefab	panelized		New Mexico	https://www.bpublicprefab.com/
Blueprint Robotics	panelized		Maryland	https://www.blueprint-robotics.com/
BuildSmart	panelized	Yes	Kansas	https://buildsmartna.com/
Collective Carpentry	panelized		British Columbia	https://collectivecarpentry.com/
Ecococon	panelized / straw	Yes	Slovakia/NY	https://ecococon.eu/us/
Ecocor	panelized	Yes	Maine	https://ecocor.us/
EkoBuilt	panelized / kits		Ontario	https://ekobuilt.com/passive-house-kit/
GO Logic	panelized		Maine	https://www.gologic.us/thegohome
Holzraum System	panelized / mass timber		Pennsylvania	https://www.holzraumsystem.com/
Legalett	panelized	Yes	Quebec	https://legalett.ca/
NotchSB / Opal Shelter	mass timber		Maine	https://www.notchsb.com/ - https://opalshelter.us/
Pheonix Haus	panelized	Yes	Colorado	https://phoenixhaus.com/
Quantum Passivhaus	panelized	Yes	Ontario	https://www.quantumpassivhaus.com/

Continuous Climate Specific Insulation Principle #1


Element #1: Climate Specific Insulation



Any Insulation is possible too - just be continuous!







Boards: Mineral Wool, Foam, Wood Fiber







Introduction to Passive House Trades

Spray Insulation: Dense Pack Cellulose is a Favorite







Dense-pack: Pump to 3.5 lbs per ft³ in walls to prevent settling







Batt Insulation (not continuous) Can play a part.







Quality Control of Batt Insulation is a Concern



Bad Installations Samples of Rigid Insulation







Introduction to Passive House Trades

Problems with Spray Foam




Introduction to Passive House Trades


Fundamental Characteristics of Enclosures

Control Layers:


- 1. Shed Bulk Water (rain coat)
- Vapor Control (prevent wetting and allow drying)
- 3. Air Control (airtightness)
- 4. Thermal Control (insulation)



"Perfect Wall" - The control layers wrap the structure and are protected by exterior cladding.




Ref http://passipedia.passiv.de/passipedia_en/




Primary air barrier at interior side of insulation - in a heating dominated climate this keeps warm moist air from condensing in the wall assembly.

Avoid Vapor Barriers in Walls & Roofs





Vinyl Wallcovering – Mold due to inwardly driven moisture trapped by the vapor impermeability of the vinyl wallcovering



Interior Polyethylene Vapor Barrier – Condensation from inwardly driven moisture


Building Science Corp.

#1: Try to keep water out, BUT...#2: When* it gets in, let the water dry out.


Variations on Layering below is typical

Shed Water Vapor Control Air Control Thermal Control

- 1. Back Vented Rainscreen
- 2. Continuous Insulation
- 3. Waterproofing
- 4. Structure (w/ insulation)
- 5. Airtightness
- 6. Service Cavity (to protect the airtight layer)
- 7. Interior Finish



Brick, Panels & Siding on Masonry & Framing Walls









STRUCTURAL INSULATED PANELS (SIPS)





Double Stud Walls






Introduction to Passive House Trades

Larsen Truss or I-Joist Outrigger on Stud Wall






For a thick parka!

Insulated Concrete Form









SOURCE: Thermohouse ICF

Insulation under the entire slab on grade.











Mineral Wool

Thermal Bridge Free Principle #2

Element #2: Thermal Bridge Free Construction





Element #2: Thermal Bridge Free Construction



Thermal 'Shortcuts' Through the Envelope Insulation







What's a Thermal Bridge?

Part of the building envelope where the otherwise uniform thermal resistance is significantly reduced by:



full or partial penetration of the insulating layers by materials with a different thermal conductivity



and/or


a change in thickness of the insulating layers




and/or

a difference between internal and external areas, such as occurs at wall/floor/ceiling junctions.

The Quality & Lengths of Joints Add Up!







Repeating Thermal Bridges (clear field)

Wood stud wall, insulated cavity:


Nominal R-value (through cavity): 22.3 Actual R-value (incl. framing): 19.0







Steel stud wall, insulated cavity:


Nominal R-value (through cavity): 22.3 Actual R-value (incl. framing): 11.6






Point Thermal Bridges at Structure & Attachments





Identify all the locations of possible thermal bridges



Source: PHI, Author: JS

fRsi helps guide insulation levels at weak points.

$$f_{Rsi} = (t_{si} - t_{e}) \div (t_{i} - t_{e})$$

With:


f_{Rsi} Temperature factor at the internal surface

t_{si} Interior Surface Temp

t_e Exterior Design Temp


t_i Interior Design Temp








Note: For f_{Rsi} calculation, surface temps and exterior conditions must be modeled as per ISO 10211 & 13788

Advanced Framing











Double Stud Window Detail



Thermal Bridge Free Attachments








Brick Ties

Basalt Wall Ties

Thermal
Conductivity (k):
0.4 Btu/hr.ft.°F



Stainless steel Wall Ties


Thermal Conductivity (k): 9.8 Btu/hr.ft.°F

25 times more heat loss!


Facade Clips




Brick Shelf



SOURCE: Ferro Fast



Parapet Improvement



AAC Block


Autoclaved Aerated Concrete Block (AAC)

- Increased thermal insulation (roughly R-1)
- Structural thermal break material
- Lightweight, workable with hand tools
- Fireproof
- Less Portland cement
- Noise reduction
- Moisture regulation



Balconies






Source: Contech Accessories and Schock

Structural Breaks






Steel to Steel Connections: Balcony Attachments (images courtesy of Contech Accessories and Shock)

Thermal Bridge Free Eaves






Don't undermine insulation w/ metal parts



Foundation Edge: Slab on Grade



Source: WarmForm

Thermal Break Materials: Armatherm








Airtightness Principle #3

Element #3: Airtight/Smoke Tight Enclosure




0.60 ACH 50: There will be a test!


- Care toward details and workmanship make the difference.
- Experienced teams can rely on a good result with final test.
- Teams new to passive house will want to plan for preliminary tests while air barrier remains exposed and repairable.
- Teams must recognize the air barrier, protect it, and report any damages.
- The building can never be too airtight.



Date of Tes	t: 1/11/2013 Test File: 15 P	Park Place Test			
Technician: Nicholas Abreu Project Number: 15 Park Place		Signature: Nulsole ar			
Customer:	Placetailor 67 Dudley Street Roxbury, MA 02119 Phone: 617-639-0633 Fax:	Building Address: 15 Park Place Somerville, MA 02144			
Test Results at 50 Pascals:		Depressurization	Pressurization	Average	
cfm (Airllow) ACH50 cfm/fi² (Floor Area) cfm/fi² (Floor Area) cfm/fi² (Surface Area) Leakage Areas: Canadian EqLA @ 10 Pa (in²) in²/fi² Sufface Area		80 (+/- 0.6 %) 0.38 0.0609 0.0154 7.7 (+/- 2.5 %) 0.0015	101 (+/- 0.5 %) 0.48 0.0770 0.0194 8.7 (+/- 2.6 %) 0.0017	91 (+/- 0.4 %) 0.43 0.0689 0.0174 8.2 (+/- 1.8 %) 0.0016	
LBL ELA @ 4 Pa (in²) in²/ft² Surface Area		3.9 (+/- 4.0 %) 0.0008	4.2 (+/- 4.0 %) 0.0008	4.0 (+/- 2.8 %) 0.0008	
Building Le	eakage Curve:				
Flow Coefficient (C) Exponent (n) Correlation Coefficient		5.2 (+/- 6.2 %) 0.698 (+/- 0.016) 0.99959	5.1 (+/- 6.1 %) 0.763 (+/- 0.015) 0.99965	5.2 (+/- 4.3 %) 0.730 (+/- 0.011)	
Test Standard:		E779-10	E779-10 Decressurization and Pressurization		



Airtightness is a SYSTEM



Ref http://passipedia.passiv.de/passipedia_en/

Membranes, tapes, caulks and sprays.

Air Barrier: Fluid Applied









Air Barrier Materials: Membranes













Inboard, Outboard / Reinforced, Self-Adhered / Vapor Control

Airtightness: Sheathing, Plaster and Concrete









Air Barriers?





?????????????????

Don't Use Sacrificial layers as air barrier.

Protect Airtight Layer & Minimize Penetrations!







Ducts, Pipes, Wires: Flexible & Long Lasting















Connections: Use flexible materials/connections











Directions and Help

- Always consult and follow the manufacturer's data sheet and directions.
- Involve product reps as often as needed for assistance.

AIR & VAPOR BARRIER

Barrithane VP

Substrate Inspection

Shall be cured in place 3 days minimum. It shall be smooth, with sharp protrusions such as cold joints ground flush. Honeycomb and holes/ cracks shall be filled with grout or mortar.

Concrete Masonry Unit (CMU)

Mortar joints shall be struck flush or tooled and shall be free of voids. Mortar droppings shall be removed from brick ties and all other surfaces accepting Barrithane VP and CCW accessories.

Gypsum Sheathing

Sheathing boards shall be flush at joints, with gap between boards according to building code and sheathing manufacturer's requirements. Sheathing boards shall also be securely fastened to the structure with proper fastener type, technique and spacing according to building code and sheathing manufacturer's requirements. Sheathing boards shall be repaired or replaced if inspection reveals moisture damage, mechanical damage or if sheathing boards have exceeded the exposure duration or exposure conditions as required by the sheathing manufacturer.

OSB, Plywood, Lumber, Pressure-Treated Wood

Wood sheathing inspection carries the same protocol given for gypsum sheathing. Also, moisture content, measured with a wood moisture meter in the core of the substrate, shall be below 20%. Do not cover any wooden materials with Barrithane VP or CCW accessories if moisture content is 20% or above. Do not encapsulate wood (such as nailers) with membrane, as this will cause premature rot. In most cases fire-treated and pressure-treated wood must be kiln dried to accommodate the less than 20% moisture content requirement.

Before application, obtain full, safe access to the area and mask adjacent surfaces to protect from splashes or drips. Verify that the product is within shelf life, as indicated on the product label.

The following conditions shall be detailed in accordance with Barrithane VP standard details:

- . Sheathing joints: cover with 2" width tooled ribbon of Barribond or cover with embedded 4" width strip of DCH Reinforcing Fabric
- . Rough openings, pipe/duct penetrations, sheathing inside/outside corners shall be treated with one of these methods: 1) 705 FR-A/705 FR-A XLT strip: 2) Trowel application 40 mils wet thickness of Barribond or: 3) Single or multiple costs of Barrithane VP to build minimum 40 mils total wet thickness. If method 2 or 3 is used, fill all cracks and holes with Barribond and coat raw edges of gypsum sheathing with CCW contact adhesive.
- . Expansion joints, control joints, termination at head/foot of wall. transitions of dissimilar materials: 705 FR-A/705 FR-A XLT strip bearing 3" onto each side of joint.

Prepare wall substrates accepting CCW self-adhered flashings with CCW-702, CCW-702 LV, CCW-702 WB, CAV-GRIP or Travel-Tack* contact adhesive. Prepare cured Barrithane VP membrane accepting CCW selfadhered flashings with CAV-GRIP or Travel-Tack contact adhesive.

Corner treatments shall cover the transition and extend at least 3 inches on each side. Rough opening treatment shall extend 3 inches minimum onto the wall and shall return into the rough opening deep enough to provide continuous seal of the fenestration to the air barrier. Consult Barrithane VP details for more information. All terminating edges of CCW self-adhered flashing shall be covered with a 1" width tooled ribbon of Barribond.

Onen neil and apply Parrithana VP using a point roller or housh. On place







Not frozen over Airsealed buck ioints









Swept clean

High Performance Windows & Doors Principle #4

Element #4: High-Performance Windows w/ Solar Protection




Extensions of Insulation & Airtightness




Interior 68°F Exterior 23°F

With high performance glass frames are the weakest part of the window assembly


PH Window Performance



Solar Heat gain through the glass **SHGC**




Heat Loss through the glass, frame, and spacer/installation thermal bridges **U-Value**



U-0.118

U-0.145




Less Frame = Better Performance

PH Windows






Certified Window Example Certificate



https://database.passivehouse.com/en/components/list/group 4?



Traditional vs Passive Windows




Traditional Double Hung



Tilt and Turn


PH Comfort and Hygiene Criteria

- 1. Comfort Criterion- The minimum average window surface temperature can be no lower than 7.6°F than the average interior surface temperature. Based on the installed U value of a window.
- 2. Hygiene Criterion- sets limits that restrict the minimum interior surface temperature at the coldest point of the interior surface per climate zone, eliminating the potential for condensation avoiding mold growth. Measured by climate specific temperature factors (f_{Rsi}).






Install Conditions



 $U_{w-installed} = 0.151 \text{ Btu/hr.ft}^2.^{\circ}\text{F}$ $(R_{w-installed} = 6.62 \text{ hr.ft}^2.^{\circ}\text{F/Btu})$

Poor Installation




 $U_{w-installed}$ = 0.148 Btu/hr.ft².°F ($R_{w-installed}$ = 6.76 hr.ft².°F/Btu)

Recommended Installation


U_{w-installed} = 0.215 Btu/hr.ft².°F (R_{w-installed} = 4.65 hr.ft².°F/Btu)

Poor Installation


Double Stud Window Detail



Window in Masonry Layer



Window External to Masonry Layer



Window Placed Outboard in Insulation Layer



Attachment with metal brackets (to be covered with insulation later)

Dense insulation blocking such as 'Compact' foam used to support the weight of the window whilst fixing into place

Retrofit example

Pre taping for tight conditions.





Window Air Sealing Example





No Metal Sill Pans!








Hansa Windows a contract to the factor of the second

Window Install Testing: Sometimes Necessary








Many manufacturers to choose from


Manufacturer/Supplier	Speciality	Offers PHI Certified Components	HQ Location	Link
Alpen		Yes	Colorado	https://www.thinkalpen.com/
Amberline			Massachussetts	https://amberlinewindows.us/
Bewiso	simulated double-hung		Austria/NY	http://www.bewiso.eu/
Cardinal	glazing, spacers	Yes	Minnesota	https://www.cardinalcorp.com/
Cascadia	fiberglass		British Columbia	https://www.cascadiawindows.com/
Deceuninck		Yes	Ohio	https://deceuninckna.com/
Eco Windows			Connecticut	https://ecowindowsusa.com/
Edge-Tech	spacers		Texas	https://www.quanex.com/product/for-architects/warm-edge- spacers/
ENERsign		Yes	Germany/CO	https://www.enersign.com/en/
EuroLine Windows		Yes	British Columbia	https://euroline-windows.com/
Fakro	skylights	4445	Poland/Illinois	https://shop.fakrousa.com/
Gamma North America	,	Yes	Ontario	https://gammana.com/
GlassCurtain	curtain wall		Alberta	https://glascurtain.ca/
Hella	exterior shading	Yes	Germany/MN	https://www.tannerbp.com/hella-exterior-blinds
Ikon Windows			New York	https://www.ikonwindows.com/
Inline Fiberglass	-		Ontario	https://www.inlinefiberglass.com/
Innotech Windows		Yes	British Columbia	https://www.innotech-windows.com/
Internorm		Yes	Germany/NY	https://www.sashandframe.com/
Intus Windwos		Yes	Virginia	https://www.intuswindows.com/
Lamilux	skylights/glass roofs	Yes	Germany/NY	https://475.supply/collections/lamilux
Makrowin		Yes	Slovakia/MA	https://www.eas-usa.com/
Morgan Advanced Materials – Vacupor			UK/MN	https://www.tannerbp.com/
Nord Windows & Doors		Yes	Alaska	https://aknordwindows.com/
NZP Fenestration		Yes	Quebec	https://nzpfenestration.com/en/
Optiwin		Yes	Germany/Wisconsin	https://www.heritagewindow.com/
PH Tech			Quebec	https://phtech.ca/en/
Raico	curtain wall	Yes	Germany/MN	https://www.tannerbp.com/
Rangate	Annual Control of the	Yes	British Columbia	https://rangate.com/
Rehau		Yes	Switzerland/NY	https://www.rehau.com/us-en/windows
Schueco		Yes	Germany/CT	https://www.schueco.com/ca/company/schueco-usa
Smartwin			Germany/KS	https://advantagewoodwork.com/
Swissspacer	spacers	Yes	Switzerland	https://www.swisspacer.com/en-us/
Tanner			Minnesota	https://www.tannerbp.com/
Technoform	spacers		Germany/OH	https://www.technoform.com/en
Viking		Yes	Estonia/CO	https://www.egresswindowtastic.com/
Westeck		Yes	British Columbia	https://www.westeckwindows.com/
Wythe Windows		Yes	New Jersey	https://www.wythewindows.com/
Yaro			Massachussetts	http://www.yarowindows.com/
Zola	simulated double-hung	Yes	Colorado	https://www.zolawindows.com/





Examples from...


















Mass Timber and Control Layers







Across Construction Types...











Steel








Mechanical Systems

Principle 5 + Other Systems

VentilationPrinciple #5

Element #5: Hygienic Ventilation w/ Heat Recovery




Passive House Ventilation

- Good air quality
- Continuous Operation
- Balanced ventilation
- Heat/Energy recovery

Heating, cooling & domestic hot water systems are important but come after addressing the enclosure and ventilation performance.

5.



PH Ventilation Design Criteria



- Energy recovery > 75%
- Fan power efficiency < 0.765 W/CFM.
- Supply > 62°F on winter design day.
- Supply air to all served spaces: living rooms, bedrooms, offices, classrooms etc...
- Exhaust from all services spaces: kitchens, bathrooms, utility rooms etc...
- Overall supply and exhaust must be balanced to be with within 10% of each other.



¹⁾ Carry-over from extract to supply air side.
²⁾ Due to heat exchanger condition the risk of carry-over from extract air to supply air side oxists, in order to avoid carry over into the supply air side, pressure

air side exists. In order to avoid carry over into the supply air side, pressure conditions in the device must be set as given by the manufacturer.


3) At the lower airflow rate might be exceeded.

cool, temperate climate

CERTIFIED
COMPONENT
Passive House Institute

www.passivehouse.com

Heat Recovery Ventilation Unit




Balanced Ventilation

Centralized: One main ventilator unit for the entire building

Decentralized:

Multiple ventilators distributed throughout the building



ERV/HRV - Single Unit











Source: Zehnder, Lunos, Renewaire

PH Ventilation Systems Considerations

- Duct insulation for intake and exhaust ducts with vapor-tight seal.
- Sound level ventilation system must not be noisy.
 - ≤ 25 db(A): supply air to rooms
 - ≤ 30 db(A): rooms in non-residential buildings and exhaust air rooms in residential buildings
- Filtration for both supply and exhaust air.
 - MERV 13-14 to filter incoming air pollutants
 - MERV 6 to filter Extract return (only needed to protect heat exchange core)






Intake and exhaust duct insulation



Merv 13 filter sample

Single Family Ventilation Layout

This 3-dimensional model of the ventilation system helped the design team avoid structural and other building services conflicts, balance duct lengths for system efficiency and easy provisioning, and ensure that the mechanical room was adequately dimensioned and laid out.



Recirculating Kitchen Venting

 Extract grille in ceiling connected to ERV and working 24/7

 Recirculating hood with charcoal filter directly above the stove


 Operable window for purge ventilation if needed




Duct Sealing & Testing for Large Buildings

- Ductwork needs to be airtight!
 - mastic duct sealant
 - mastic tape
 - preformed and insulated duct layouts
- Recommend to perform duct leakage testing to ensure system is well sealed.
- Balanced air flows is critical.
 - One strategy is to use Constant Airflow Regulators (CARs)

- Long ductwork requires careful planning
- Ensure CxA knows what the protocol is for measuring outlets – all outlets must be turned on, not just the suite being measured




Proper duct sealing will only get you so far,
 a good design is always important!



Ventilation Balancing & Report



Zero pressure compensating flow measuring instruments are the most accurate



anemometers typically allow measurement of volumetric flow rate, air flow speed and temperature



Training for commissioning agents is vital for accurate results

VENTILATION

Manufacturer/Supplier	Speciality	Offers PHI Certified Components	HQ Location	Link
Acin	air flow meter		Netherlands	https://acin.nl/en/
Aeroseal	duct sealing (central systems)		Ohio	https://aeroseal.com/
Aldes	constant airflow regulator	Yes	Quebec/FL	https://www.aldes-na.com/
Brink		Yes	Netherlands/NY	https://475.supply/collections/brink
Ephoca	through wall		Italy	https://ephoca.com/
Lunos			Germany/NY	https://475.supply/collections/lunos
Minotair Ventilation Inc.			Quebec	https://www.minotair.com/home_us/
Oxygen 8		Yes	British Columbia	https://oxygen8.ca/
Swegon		Yes	Sweden/Ontario	https://www.swegon.com/na/
Ventacity		Yes	Oregon	https://www.ventacity.com/
Zehnder		Yes	Netherlands/ME	https://zehnderamerica.com/

FINAL PROTOCOL WORK SHEET for Ventilation Systems: Initial Start-up Supply- / Extract-Air Ventilation System with Heat Recovery

Project		Initial Start-up	
Object	End-terrace house	Company	Passive House Vent
Location Street, No.:	Passive street 123	Person in Charge:	John Smith
Location Postcode, Town	12345 Passive City		Passive street 12
Building Owner Name:	John Doe	Postcode, City:	12345 Passive City
Building Owner Phone No.:		Phone No.:	00000
Year of Construction	2017	Date:	07 / 01 / 2017

Manufacturer Passive House Ventilation Passive House unit Control No.:

1. Record of the air flow volumes, supply and extract air

Nr.	Room	Design			Measureme	ent 1	Measurmer	nt 2	Measurem	ent 3	ype of Valve Adjustment	Flow-Through	Noise	Filter	Filter
		V _{SU}	V _{EX}	V _{THROUGH}	V _{SU}	V _{EX}	V _{SU}	V _{EX}	V _{SU}	V _{EX}		VTHROUGH		Grade	Clean?
		m³/h	m³/h	m³/h	m³/h	m³/h	m³/h	m³/h	m²/h	m³/h		m/s	dB(A)		
-1	Hobby room	35			45.1		30		37		et nozzle	0.6	20	F7	yes
2	Storage room		20			36		26		21	Poppet Exhaust Air	0.8	22	G4	yes
3	Technical space		20			41.2		18		20.3	Poppet Exhaust Air	0.7	22	G4	yes
4	Office	20			31.6		19.6		19.6		et nozzle	0.6	20	F7	yes
5	Living / kitchen	60	60		62.4	45.2	57.4	65.3	59.5	61.2	et nozzle/poppet exhaust air	1.0	20	F7/G4	yes
6	Master bathroom		40			12.7		34.2		41	Poppet Exhaust Air	0.6	22	G4	yes
7	Bedroom 2	20			21.9		26		20.7		et nozzle	0.6	20	F7	yes
8	Bedroom 3	20			28		26.9		19.1		et nozzle	0.6	20	F7	yes
9	Master bedroom	25			20.6		26.1		26.1		et nozzle	0.7	20	F7	yes
10	Bathroom		20			40.1		22.1		19.9	Poppet Exhaust Air	0.6	22	G4	yes
11	WC		20	1		43.6		23		19.6	Poppet Exhaust Air	0.7	22	G4	yes
12															yes / no
13															yes / no
14															yes / no
15														il.	yes / no
	sum	180.00	180.00		209.60	218.80	186.00	188.60	182.00	183.00		122		1922	124

2. Balance of airflow volume		Measurement 1		Measurement 2		Measurement 3		Disbalance		e	Type of Control	Adjustment	Noise	Filter	Filter
		V _{AUL}	V _{FOL}	VALL	V _{FOL}	V _{AUL}	V _{FOL}						Measurement	Grade	Clean?
		m³/h	m³/h	m²/h	m³/h	m³/h	m³/h		_				dB(A)	To a second	
1 fresh air inlet		210		186		182			18	\	BUS		30	F7	yes
2 exhaust air outlet			219		189	-	183	1 (7.0)	BUS		30	G4	yes

3. Initial start-up accomplished according to manufacturer's specifications:

Signature:


© PHD GmbH + PHI, Darmstadt 09/2007

Sample documents for building certification @ Passive House Institute 2023 Find out more at: www.passipedia.org/certification/certified_passive_houses/example_documents

Heating & Cooling Systems

Right Size Heating & Cooling Systems

- Often up to 75% reduction in equip sizing.
- Practically any kind of heating and cooling system can be used in a Passive House.
- Critical is efficient design with relatively compact distribution and right sizing of equipment.
- Typically heat pump technology capable of providing heating and cooling.
- Typically runs separately from, and independently of, ventilation air.



Single Family: Heating, Cooling & Dehumidification


Much smaller load and great flexibility in locating distribution outlets: surface mounted, recessed, ducted.

Commissioning is critical.



Keep Ventilation Separate from Cooling

- If ducted, must keep ventilation duct work completely separate from heating / cooling system ductwork.
 - Very difficult to properly balance air flows.
 - Increased fan energy penalty from air handler running 24/7
 - More wear and tear on equipment



Exhaust air: kitchens and baths (red)

Supply air: living room and bedrooms (blue)

Heating/cooling (yellow)

Duct and Refrigerant Piping & Insulation

- Insulate all air conditioning ducts.
- Insulate all refrigerant lines.









DHW

DHW and Energy Use

Reducing the use of hot water is largely dependent on occupants, but an
efficient water heater and distribution system can still make a big difference on
the total energy used by reducing unnecessary losses.


Overall strategy:

- Minimize demand using low-flow devices
- Use small-diameter pipes
- Use the shortest possible pipe lengths
- Minimize losses through insulation
- Optional -use heat recovery from wastewater
- Optional generate hot water on-site from solar collector



Decentralized Hot Water

- Common options include
 - Conventional storage water heaters (gas, electric)
 - Tankless or on-demand water heaters (gas, electric)
 - Solar water heaters
 - Tankless coil / indirect water heaters
 - Heat pump water heaters




Combined Heat Pump System



Source: Energy Star, SANCO2

Split Heat Pump System

Minimize Pipe Runs in Design & Installation



DHW Pipe Insulation

- Insulation thicknesses to align with PHPP assumptions and local energy code requirements.
- Insulation to be continuous at all hanger locations.
- Runout piping to be fully insulated to the greatest extent possible.





Pipe Insulation

- Pipes to be insulated include:
 - Domestic hot water: typically 1" insulation for smaller pipes, 1.5" insulation for larger pipes.
 - Domestic cold water (best practice): typically 1" all locations.
 - Refrigerant lines: typically 1" insulation for smaller pipes, 1.5" insulation for larger pipes.



Source: Johns Manville

DHW – Recirculation Pumps

- Ensure DHW pump sizes align with PHPP assumptions.
- Some systems may utilize a demand recirculation system that turns off the recirc pump during periods of low DHW use.





QA/QC



Assemble the team to deliver a Passive House

- Architects
- Engineers
- Consultants
- Passive House Consultant
- Builder & Trades
- Verifier/Verification
 - Inspectors
 - Ventilation Commissioning
 - Blower door testers
- Certifier

What a team needs:

- common language
- 2. common goal: Passive House
- 3. good attitudes
- 4. enough training
- willingness to work as a team and connect the dots












Construction Schedule: Passive House line items...

Design Stage Open Items							
Close out unresolved items							
Submittals							
Verification Plan						5	
Product Specs							
Training & Mockups							
Envelope Connections							
Window Installation							
Inspections							
Representative Photos							
Ventilation							
Duct Leakage Testing							
Ventilation Commissioning							
Airtighness Testing					Î		
Connections Mockup							
Final Whole Building Blower door test							
As-Built Updates							
PHPP, Construction Drawings, Details, schedules and descriptions							
Photo "catalog"							
Builder Assurance Certificate							

Passive House Specific Verification Plan

Have explicit clarification of QA/QC procedures

- Who's responsible for what and when.
- Identify ventilation commissioning agent and blower door tester.
- Where will reports be compiled for the certifier?
- What's the proposed substitution review procedure for Passive House relevant items?
 What are those items?
- Make a formal Verification Plan



https://passivehousenetwork.org/wp-content/uploads/2024/07/Vancouver-Passive-House-Verification-Plan-Checklist-2023.pdf

Checklists for Use During Construction

 Helpful for the field verifier and the contractor to understand what is expected for the project




- Below-grade insulation
- Above-grade wall insulation
- Roof insulation
- Air barrier
- Fenestration performance values
- Duct Sealing
- Pipe insulation
- HVAC and DHW equipment
- Lighting and lighting controls

Common Difficulties & Frustrations

- Design review open items remain open.
- Proposed changes during construction are not vetted in the PHPP.
 (And maybe the PHPP was never really completed. See #1)
- Construction changes are not brought to the Certifiers attention delivering unintended consequences.
- Not certified components substituted in not vetted more unintended consequences.
- Thermal bridge calculations are not completed.
- Work is out of sequence and air barrier is covered before testing.
- 7. Photographs are not organized, for expeditious review.
- Approved submittals and as-built documentation are not submitted to the Certifier in a timely fashion.
- 9. Special conditions are not resolved early.
- 10. Team loses focus on whole building airtightness and ventilation.
- 11. Team doesn't appreciate their impact on performance results.

Submittals for Certification









1600	
3.2	Documents to be submitted
3.2.1	Passive House Planning Package (PHPP)
3.2.2	Design and planning documents
3.2.3	Standard and connection details
3.2.4	Windows and doors
3.2.5	Shading
3.2.6	Ventilation
3.2.7	Space heating/cooling, DHW and waste water
3.2.8	Electrical devices and lighting
3.2.9	
3.2.1	0 Airtightness of the building envelope
3.2.1	1 Photographs
3.2.1	2 Exceptions (only for EnerPHit)
3.2.1	3 Economic feasibility calculation (only for EnerPHit)
3.2.1	4 Verification of general minimum requirements (according to Subsection 2.4)
3.2.1	5 Construction manager's declaration



Introduction to Passive House Trades

Mock-Ups: Visual & Testing

Mock-ups can vary in terms of extensiveness.










An extensive mock-up could be a full six-sided box with various details reflected.

A simple mock-up could be the first window installed on the project.

Airtightness Plan & Culture











- Airtightness 'control station' strategically located at project
- All penetrations must be noted in writing
- Airtightness coordinator checks the log of penetrations daily and repairs holes





Protect Ventilation Performance

- a. Accommodate adequate space early in design
- b. Use high-quality units & size sufficiently
- c. Aim for PHI recommendation of <2% leakage
- d. Aeroseal ducts.

Industry standard specs for sealing can result in 30%+ leakage.







Photographs

3.2.11 Photographs

Back to compact version: ▶ 3.2.11

Criteria

Evidence of the progress of construction must be supported with photographs, but it is not necessary to provide complete photographic documentation of all measures.

Samula phalantanas

Additional requirements
The construction progress must be documented with
illustrative photographs. However, full photo-graphic
documentation of all measures is not necessary. Photos
should be taken preferably at a time when the installation
situation is not yet covered by cladding etc. Typically,
photographs of the following areas should be taken:

- Thermal insulation of the building envelope (preferably with a measuring ruler in the picture to show the insulation thickness)
 - o floor slab or basement ceiling
 - o perimeter area
 - o wall insulation
 - o roof insulation
- Product data labels of
- windows frames and glazing
- o heating and cooling units
- ventilation unit
- Insulation and attachments of the air ducts
- Insulation and attachment of heating, hot water and cooling pipes and fittings
- Other energy-relevant construction details, e.g. thermal bridges
- A checklist of the pictures of the building site to be submitted for certification can be downloaded at: www.passipedia.org
- → Passive House Certification → Building Certification
- Examples of documents that need to be submitted for certification

Building Site Photos for the Passive House Certification Please make sure that the photos can be assigned correctly. Photos of delivered insulation packages Photos of the installation isulation of the foundation area / basement e.g. under the floor slab, perimeter insulation Joint between floor slab / basement ceiling to walls and pillars (e.g. thermal break, flank inculation) Product name, thermal conductivity, thickness Photos of delivered insulation packages Photos of the installation hermal bridges hotos of thermal bridge: Balcony railings, canopies, fixed ladders, fall protection etc All places where the insulation is penetrated Photos of delivered windows + doors echnical data on glazing (glass thickness, spacers, filling gas Fechnical data on frame (description), photo of frame Photos of the installation: windows ateral, top, bottom, different installation types Fixing sun protection, fall protection Photos of the installation: doors ateral, top, bottom, different installation types Product name, thermal conductivity, thickness Photos of the installation Photos of specification plate devices (e.g. pumps, ventilation unit neater, cooling system, elevator) Photos ventilation unit ocation silencer duct insulation (thickness) Photos of sanitary pipes Insulation of hot water / solar / heating pipes storage and insulation of down waste water pipes (thickness)

Photographs of the construction process demonstrating that:
a) the specified products have been installed
b) correct installation practices have been followed

1. Photos must show the make model of the equipment

2. A description of what the photo captures must accompany each photo

All construction photos should be taken prior to interior finishes

4. Photos of all product types / variants of the following must be submitted: Each insulation product for each wall, roof, floor, and foundation type Assemblies Junctions Each junction in the building, as per Junctions worksheet Windows Each window and door type Each operable window type in fully open and tilted positions to demonstrate how far they Compensatory window heater Ventilation Systems Each type of HRV / ERV unit Outdoor and extract air filters for each HRV / ERV type Ductwork & insulation for the supply, extract, outdoor and exhaust air ducts for each HRV Duct attachements (hangers, etc) Internal and external vents / grilles, showing sufficient space between intake and exhaust Air transfer grilles AND / OR door under/overcut height rost protection system Acoustic Attenuators Supply air heater n-unit occupant control devices for each HRV / ERV type Heating and Cooling Each type of heat and cooling generator Systems ach type of humidification / dehumidification system Distribution pipe insulation product and thickness, including valves & T junctions Distribution pumps DHW Systems Each type of heat generator Each type of storage tank Insulation product and thickness of primary pipes and recirculation pipes Pipe attachments (hangers, clips, etc) Circulation pumps Sanitary system - AAVs, backwater valves, pipe insulation, alternative approach Rainwater pipes - Ptraps, alternative approach Solar thermal panels Electrical Equipment Each type of light fixture and lamp Each appliance type Elevators Solar PV panels Any other relevant equipment Airtightness Testing During search for areas of additional air leakage - showing method of detection. Shading Include photographs of: a. Each elevation of the building

b. Window and door overhangs and reveals (from exterior)

Organize daily/weekly throughout...don't wait!

Note: Typically conducted as part of inspection regime by independent verifier.

Contractor may submit photographs to document fixes.

Construction Managers Declaration

Signed Declaration

Include a completed and signed copy of the Declaration of Conformance form from the construction supervisor.

Project name:

Location:

Project name on Certification platform:

Construction manager (First name, Surname):

Project manager (First name, Surname):

Construction manager declaration

In order for the quality inspection to award the "Certified Passive House" seal for the above mentioned construction project, we hereby assure that the on-site execution is in accordance with the planning documents, technical documents and textual descriptions that have been uploaded to the Passive House Institute's certification platform up to and including // (and not marked as "obsolete").

This has been checked through regular site visits.

https://passipedia.org/ media/picopen/construction manager declaration.pdf

Construction management Date, Signature	Project management Date, Signature	

Recommendations

- Meet early with the Certifier and identify all critical items and develop a Verification Plan.
- 2. Include all necessary verification work in construction schedule.
- 3. Insist on training for the construction staff.
- 4. All subs should be aware of the project goals even if not directly related to Passive House.
- 5. Do mockups and preliminary blower door testing.
- 6. Do ventilation duct leakage testing and Aeroseal the ventilation ducts. (MF)
- 7. Maintain a dedicated inspection log for all on-site Passive House items for Contractor to address and close out.

- 8. Stay aware of what's outstanding and keep on schedule with the work.
- 9. Make submissions to Certifier in a timely manner.
- 10. Organize the photos as you go address all items outlined by the Certifier.
- 11. If you're not sure about something, ask the Certifier.
- 12. Hire a Certifier to coach team as needed.
- 13. Develop a culture that connects construction work to high-performance outcomes, including specialized training.
- 14. Empower the team.



Build a Culture of Quality!

Focus on the 5 principle drivers, and the comfort, hygiene & efficiency goals.



With focus and a little training, anyone can build a Passive House.

Resources

Resources

- 1. A Comparison of Canadian and European Energy Standards for Household Appliances-https://passivehousenetwork.org/featured/appliance-modeling-guide/
- 2. BC Hydro Building Envelope Thermal Bridging https://www.bchydro.com/content/dam/BCHydro/customer-portal/documents/power-smart/builders-developers/building-envelope-thermal-bridging-guide-v1-6.pdf
- 3. Building Certifier Scope of Services https://passivehousenetwork.org/wp-content/uploads/2024/07/Building-Certifier-Scope-of-Services-JULY-2024-UPDATE.pdf
- 4. Building Database-https://passivehouse-database.org/index.php?lang=en
- 5. Building for People-https://islandpress.org/books/building-people#desc
- Certification Criteria https://passivehouse.com/03 certification/02 certification buildings/08 energy standards/08 energy standards.html
- 7. Certification Guide https://passivehouse.com/03 certification/02 certification buildings/09 guide/09 guide.html
- Certified Components https://database.passivehouse.com/en/components/
- 9. Certifiers Globally https://passivehouse.com/03 certification/02 certification buildings/03 certifiers/01 accredited/01 accredited.html
- 10. Certified Passive House Designer Training https://passivehousenetwork.org/designer-training/
- 11. Certified Passive House Tradesperson Training https://passivehousenetwork.org/tradesperson-training/
- 12. Construction Cost Analysis of High-Performance Multi-Unit Residential Buildings in British Columbia
 - https://passivehousenetwork.org/wp-content/uploads/2024/10/CONSTRUCTION-COST-ANALYSIS-OF-HIGH-PERFORMANCE-MULTI-UNIT-RESIDENTIAL-BUILDINGS-IN-BRITISH-COLUMBIA-V3.1.pdf
- 13. Details for Passive Housees: New Buildings
 - https://www.thriftbooks.com/w/passivhaus-bauteilkatalog-neubau--details-for-passive-houses-new-buildings-kologisch-bewertete-konstruktionen--a-catalogue-of-ecologically-rated-constructions-german-edition/54431586/item/83148133/
- 14. Details for Passive Houses; Renovation https://birkhauser.com/en/book/9783035607543
- 15. Easi Guide to Passivhaus Design https://www.levittbernstein.co.uk/site/assets/files/3553/passivhaus-easi-guide_screen_portrait.pdf
- 16. High Performance Walls Study by Steven Winter Associates http://swinter.com/wp-content/uploads/High-Performance-Walls-2019-reformatted.pdf
- 17. Is Cost the Barrier to Passive House Performance?-https://passivehousenetwork.org/wp-content/uploads/2022/10/ls-Cost-the-Barrier-to-Passive-House-Performance-Mav-2021-PHN.pdf
- 18. ISO 9972 https://www.iso.org/standard/55718.html
- 19. Legalizing Mid-Rise Single-Stair Housing in Massachusetts-https://www.jchs.harvard.edu/sites/default/files/research/files/harvard_jchs_utile_boston_indicators_single-stair housing_october_10_2024.pdf
- 20. Manager Declaration Sample https://passipedia.org/_media/picopen/construction_manager_declaration.pdf
- 21. Manufacturers Directory https://passivehousenetwork.org/manufacturers-directory/
- 22. National Definition of Zero Emissions Building: https://www.energy.gov/sites/default/files/2024-06/bto-national-definition-060524.pdf
- 23. North American Certifiers Circle https://passivehousenetwork.org/wp-content/uploads/2023/01/NACC-Brochure-Jan-2023.pdf
- 24. Passipedia-https://passipedia.org/start
- 25. Passive Architecture https://issuu.com/lafamillecarbonic/docs/passive_architecture_en
- 26. Passive House Certification https://passivehousenetwork.org/certification/
- 27. Passive House Criteria for Buildings-https://passivehouse.com/03_certification/02_certification buildings/08_energy_standards/08_energy_standards.html
- 28. Passive House Definition https://passipedia.org/basics/the passive house definition
- 29. Passive House Details https://www.amazon.com/Passive-House-Details-Solutions-High-Performance/dp/1138958263
- 30. Passive House-Historical Review-https://passipedia.org/basics/the_passive_house historical review
- 31. Passive House Planning Package (PHPP) https://passivehouse.com/04_phpp/04_phpp.htm
- 32. Safe at Home PHN Report https://passivehousenetwork.org/safe-at-home/
- 33. Sample Submission Documents https://passipedia.org/certification/certified_passive_houses/example_documents
- 34. Summer Comfort https://passipedia.org/planning/summer comfort
- 35. The Greenest Home https://www.amazon.com/Greenest-Home-Superinsulated-Passive-Design/dp/1616891246
- 36. Thermal Comfort https://passipedia.org/basics/building_physics basics/thermal_comfort
- 37. Understanding Passivhaus https://www.firstinarchitecture.co.uk/understanding-passivhaus/
- 38. Unlocking livable, resilient, decarbonized housing with Point Access Blocks-https://www.larchlab.com/wp-content/uploads/2022/01/Eliason_CoV-Point-Access-Blocks-report_v1.2.pdf
- 39. Vancouver Passive House Verification Plan Checklist-https://passivehousenetwork.org/wp-content/uploads/2024/07/Vancouver-Passive-House-Verification-Plan-Checklist-2023.pdf
- 40. Ventilation Duct Leakage Testing https://passivehousenetwork.org/product/multifamily-ventilation-duct-leakage-targets-strategies-and-lessons-learned/

Thank you.



Questions about Title 24?

3Correction



3C-REN offers a free Code Coach Service

Online:

3c-ren.org/code

Call:

805.781.1201

Energy Code Coaches are local experts who can help answer your Title 24 Part 6 or Part 11 questions.

They can provide code citations and offer advice for your res or non-res projects.

Closing



Continuing Education Units Available

Contact dresurreccion@co.slo.ca.us for AIA LUs

Coming to Your Inbox Soon!

Slides & Recording

Get Passive House Certified!

(FREE for Ventura, Santa Barbara, & San Luis Obispo County)

- o Certified Passive House Designer/Consultant Pacific Fall 2025 Cohort
- 5-Day Passive Design/Build Bootcamp in Ventura (Sept 29 Oct 3)

Upcoming Courses:

- Aug 20 Best Practices for Hot Water Distribution
- Aug 26 Ask The Experts : Enclosures

Any phone numbers which in California name!



Thank you!

More info: 3c-ren.org

Questions: info@3c-ren.org

Email updates: 3c-ren.org/newsletter



TRI-COUNTY REGIONAL ENERGY NETWORK
SAN LUIS OBISPO • SANTA BARBARA • VENTURA

